SECURITY CO	AD-A234	049 -	والمراجع			
•	/\D /\LU	CUN	MENTATION	PAGE 7	TIO CHE	PRODV
1a. REPORT SECUL Unclassified	RITY CLASSIFICATION	-	16. RESTRICTIVE		ilo faka	
28. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT			
26. DECLASSIFICATION / DOWNGRADING SCHEDULE			Distribution Unlimited			
4. PERFORMING ORGANIZATION REPORT NUMBER(S)			S. MONITORING ORGANIZATION REPORT NUMBER(S)			
1990-24						
61. NAME OF PERFORMING ORGANIZATION 66. OFFICE SYMBOL			7a. NAME OF MONITORING ORGANIZATION			
University of Pennsylvania		(If 3pplicable)	ONR			
University o Department	, State, and IP Code) of Pennsylvania of Chemistry 1, PA 19104-6-23	7b. ADDRESS (City, State, and 21P Code)  800 N. Quincy Street Arlington, VA 22217-5000				
88. NAME OF FUN ORGANIZATIO	NDING/SPONSORING N DARPA	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
N ADDRESS (CIN	, State, and ZIP Code)	10. SOURCE OF FUNDING NUMBERS				
1400 Wilson Blvd. Arlington, VA 22209-2308			PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
12. PERSONAL AL  13a. TYPE OF REI Technical  16. SUPPLEMENT.	PORT 13b. TIME C FROM 06-C	Tanner, N. Theophilos  OVERED  11-90 TO 10-31-91  18. SUBJECT TERMS ( stretched highly-stretched highly-stre	14. DATE OF REP March 18  ARTOR  Continue on rever	ORT (Year, Month 8, 1991	and identify by blure and polariza	E COUNT
We have measured the temperature and polarization dependence of the infrared absorption in 500%-stretched highly-conducting trans-(CH) <sub>x</sub> , doped chemically with iodine to levels up to 6% (1) The dc conductivity for the 6%-doped sample was ~ 10 000 Ω <sup>-1</sup> cm <sup>-1</sup> at 300 K.  These samples have highly anisotropic infrared conductivity, with substantially greater σ <sub>1</sub> (ω) for polarization parallel to the chain direction. The 300 K frequency-dependent conductivity has a narrow Drude-like peak at zero frequency above which is a broad "midgap" band with the usual doping-induced vibrational modes superimposed. When the temperature was lowered, the far-ir conductivity decreased (in accord with dc measurements). The Drude-like peak was not seen below 200 K.						
	ON/AVAILABILITY OF ABSTRACT			SECURITY CLASSIF	ICATION	
	FIED/UNLIMITED   SAME AS RESPONSIBLE INDIVIDUAL	S   Linclassified   22b. TELEPHONE (Inc.) under Area Code)   22c. OFFICE SYMBOL ,				
Alan G. Ma			1	98-8307		•
DD FORM 147	73, 84 MAR 83 A	APR edition may be used to All other editions are		SECURIT	Y CLASSIFICATIO	N OF THIS PAGE

#### OFFICE OF NAVAL RESEARCH

GRANT NO.: N00014-90-J-1559

R & T CODE NO.: A400004DF3

TECHNICAL REPORT NO.: 1990-24

### "POLARIZED ABSORPTION IN ORIENTED 'NEW' (CH)x"

by

H.S. Woo, D.B. Tanner, N. Theophilou and A.G. MacDiarmid

Accepted for Publication in Synthetic Metals, In Press (1990)

University of Pennsylvania Department of Chemistry Philadelphia, PA 19104-6323

March 18, 1991

1-A

Reproduction in whole or in part is permitted for any purpose of the United States Government.

This document has been approved for public release and sale; its distribution is unlimited.



ICSM. Tubiger Synthetic Metal, In Press (1990).

'JAN 0 9 1983

# POLARIZED ABSORPTION IN ORIENTED "NEW" (CH),

H.S. WOO and D.B. TANNER,

Department of Physics, University of Florida, Gainesville, FL 32611

N. THEOPHILOU and A.G. MacDIARMID,

Department of Chemistry, University of Pennsylvania, Philadelphia, PA 19104

#### Abstract

We have measured the temperature and polarization dependence of the infrared absorption in  $\sim 500\%$ -stretched highly-conducting trans-(CH)<sub>x</sub>, doped chemically with iodine to levels up to 6% (I<sub>3</sub><sup>-</sup>). The dc conductivity for the 6%-doped sample was  $\sim 10\,000~\Omega^{-1} {\rm cm}^{-1}$  at 300 K. These samples have highly anisotropic infrared conductivity, with substantially greater  $\sigma_1(\omega)$  for polarization parallel to the chain direction. The 300 K frequency-dependent conductivity has a narrow Drude-like peak at zero frequency above which is a broad "midgap" band with the usual doping-induced vibrational modes superimposed. When the temperature was lowered, the far-ir conductivity decreased (in accord with dc measurements). The Drude-like peak was not seen below  $\sim 200~{\rm K}$ .

### 1. Introduction

About four years ago, Naarmann and Theophilou<sup>1</sup> described a method of preparing high-density  $(CH)_x$  which, when doped, has conductivity considerably higher than that of Shirakawa<sup>2</sup>  $(CH)_x$ . Several variations for preparing this "new"- $(CH)_x$  have been reported, giving stretch-oriented samples conductivities in the 10 000-100 000  $\Omega^{-1}$ cm<sup>-1</sup> range.<sup>1,3,4,5</sup> In this paper we present the infrared properties of "new"- $(CH)_x$ .

## 2. Experimental

Free-standing "new"-(CH)<sub>x</sub> films were prepared at Penn as previously described.<sup>3</sup> The undoped polymers were mechanically stretched up to  $5.5 \times (550\%)$ . The doping was carried out at Florida, immediately prior to the infrared measurements. We tried both vapor-phase and solution-phase doping. With vapor-phase doping we were only able to reach dopant levels of  $\approx 2\%$  I<sub>3</sub>, well below the 6% levels achieved in Shirakawa (CH)<sub>x</sub> by the same technique. Solution-phase doping, from a I<sub>2</sub>/CCl<sub>4</sub> saturated solution, was much more successful. One hour immersion in this solution, followed by a 1 minute wash with CCl<sub>4</sub> and 5-10 minutes drying in a weak Ar stream, led to dopant levels of 6%, measured by weight uptake. Typical




Fig. 1. Temperature dependence of the dc conductivity of oriented "new"-(CH)x.




Fig. 2. Absorption coefficient of "new"- $\{CH(I_s)_{0.36}\}_x$  for  $\vec{E} \parallel$  and  $\vec{E} \perp$  to the stretching direction.

dc conductivity data are shown in Fig. 1. The conductivity decreases on cooling, as has been previously reported.<sup>1,3,4</sup>

We measured the absorbance or the reflectance (depending on frequency and doping level) at temperatures between 80 and 300 K and at frequencies between 80 and 24 000 cm<sup>-1</sup> (0.01-3 eV). To correct for scattering from rough surfaces, the reflectance of Al-coated samples was used for normalization. Kramers-Kronig analysis of the reflectance gave the optical constants.

#### 3. Results

Fig. 2 shows the absorption of heavily-doped "new"-(CH)<sub>x</sub> for two polarizations. A strong peak at 790 cm<sup>-1</sup>, mostly polarized along the chain, is introduced by the doping. The usual doping induced vibrational modes at 900 (quite broad) 1290, and 1380 cm<sup>-1</sup> can also be seen.<sup>6,7,8</sup> The intensity of these modes increases linearly upon doping up to 6 %.

A strong broad band is seen around 500 cm<sup>-1</sup>, increasing in intensity with decreasing temperature. Tanaka et al.<sup>9</sup> have observed similar behavior in  $I_3$ -doped Shirakawa (CH)<sub>x</sub>. The

band is present only in doped samples. The polarization dependence implies that this band is characteristic of the polymer chain. We speculate that it is a pinning mode, due to trapping of charge carriers by Coulomb interaction with the dopant ions and by barriers along the chains. The increase in infrared oscillator strength with decreasing temperature is accompanied by a decrease in the dc conductivity.




Fig. 3.  $\sigma_1(\omega)$  ( $\vec{E}$  || to the stretching direction) for undoped and doped "new"-(CH)<sub>x</sub>.

Fig. 3 shows the chain-axis  $\sigma_1(\omega)$  over 80-24 000 cm<sup>-1</sup> for an undoped and a 6% doped sample. Above the doping-induced modes there is a "midgap" band at 5000 cm<sup>-1</sup> (0.6 eV, somewhat smaller than half the 1.4-1.8 eV gap). A midgap absorption<sup>10</sup> is a universal feature of doped-(CH)<sub>x</sub>, even at the highest doping levels.<sup>8,11</sup> This midgap band decreases the oscillator strength of the interband transitions of the undoped polymer (in some cases to zero<sup>8</sup>) and shifts it to higher energies.

Fig. 4 shows the low-frequency part of the conductivity for 6% doping. Data are shown at 300 K for two polarizations. The anisotropy  $(E \parallel /E \perp)$  at 1380 cm<sup>-1</sup> is  $\approx$  26.

The most interesting feature in Fig. 4 is the upturn in  $\sigma_1(\omega)$  at low frequencies. This is interpreted as a Drude-like peak in  $\sigma_1(\omega)$ , associated with the free carriers. (We note that at these low frequencies, the reflectance is large, > 95% and the error in absolute reflectance—or rather in 1-R which is the "signal" in this case—is relatively large, so that the accuracy of the Kramers-Kronig results in this region is no better than  $\pm 25\%$ .) The width of the free carrier peak is very narrow, perhaps  $\sim 100~\text{cm}^{-1}$ . At  $\omega = 0$ , the conductivity is  $7000~\Omega^{-1}\text{cm}^{-1}$ , a bit smaller than the measured room temperature conductivity of this sample, which was  $10\,000~\Omega^{-1}\text{cm}^{-1}$ . (See Fig. 1.) This free-carrier peak is not seen in ordinary (CH)<sub>x</sub> because the do conductivity is so much smaller. With decreasing temperature, the do conductivity of "new"-(CH)<sub>x</sub> decreases, and the oscillator strength of the free carrier absorption is transferred into the pinning mode, as shown in Fig. 2.




Fig. 4.  $\sigma_1(\omega)$  for  $\vec{E} \parallel$  and  $\vec{E} \perp$  to the stretching direction for 6% I<sub>3</sub>-doped "new"-(CH)<sub>x</sub>.

### 4. Discussion

Despite the significant differences in dc conductivity, the infrared absorption of "new"- $(CH)_x$  resembles closely that of ordinary  $(CH)_x$ . There is only a small amount of temperature dependence. The exception is in the far infrared, where at 300 K there is a narrow, Drude-like peak in  $\sigma_1(\omega)$ . With decreasing temperature, the oscillator strength associated with this peak moves into the pinning mode at 500 cm<sup>-1</sup>.

## Acknowledgements

Work supported by DARPA URI grants (to Florida and to Penn/OSU) monitored by ONR.

### References

- 1. H. Naarmann and N. Theophilou, Synth. Met. 22, 1 (1987).
- 2. K. Soga, S. Kawakami, and H. Shirakawa, Macromol. Chem. Phys. 71, 4614 (1979).
- 3. N. Theophilou et al., Synth. Met. 28, D35 (1989).
- 4. N. Basescu et al., Synth. Met. 28, D43 (1989).
- 5. A.G. MacDiarmid and A.J. Epstein in Conjugated Polymeric Materials: Opportunities in Electronics, Optoelectronics, and Molecular Electronics, edited by J.L. Brédas and R.R. Chance (Kluwer Academic Publisher, Amsterdam, 1990), p. 53.
- 6. C.R. Fincher, Jr. et al., Phys. Rev. B 19, 4140 (1979).
- 7. A.J. Epstein et al., Phys. Rev. Lett. 50, 1866 (1983).
- 8. X.Q. Yang et al., Solid State Comm. 61, 335 (1987).
- 9. J. Tanaka et al., J. de Physique 44, C3-279, (1983).
- 10. H. Suzuki et al., Phys. Rev. Lett. 45, 1209 (1980).
- 11. D.B. Tanner et al., Synth. Met. 28, D141-D146 (1989).